CERTIFICATEOF COMPLIANCE



Wilkhahn

Timetable™ - 610 range

4941-410

Certificate Number

27 Aug 2008 - 10 Oct 2023

Certificate Period

Certified

Status

UL 2818 - 2022 Standard for Chemical Emissions for Building Materials, Finishes and Furnishings

Commercial furniture and furnishings are tested in accordance with ANSI/BIFMA M7.1-2011(R2016) and determined to comply with ANSI/BIFMA X7.1-2011(R2016) and ANSI/BIFMA e3-2019 Credit 7.6.1 in a Private Office environment.

Products tested in accordance with UL 2821 test method to show compliance to emission limits in UL 2818, Section 7.1.





GREENGUARD Certification Criteria for Individual Office Furniture Products

| Criteria | CAS Number | Maximum Allowable Emission Factor | | |
|---------------------|------------|-----------------------------------|----------------|------------|
| | | Open Plan | Private Office | Units |
| TVOC _(A) | - | 345 | 694 | μg/m²*hr |
| Formaldehyde | 50-00-0 | 42.3 | 85.1 | μg/m²*hr |
| Total Aldehydes (B) | - | 2.8 | 5.7 | μmol/m²*hr |
| 4-Phenylcyclohexene | 4994-16-5 | 4.5 | 9.0 | μg/m²*hr |
| Individual VOCs (C) | - | 1/10th TLV | 1/10th TLV | - |

⁽A) Defined to be the total response of measured VOCs falling within the C6 – C16 range, with responses calibrated to a toluene surrogate.





⁽B) The sum of all measured normal aldehydes from formaldehyde through nonanal, plus benzaldehyde, individually calibrated to a compound specific standard. Heptanal through nonanal are measured via TD/GC/MS analysis and the remaining aldehydes are measured using HPLC/UV analysis.

⁽C) Allowable levels for chemicals not listed are derived from 1/10th of the Threshold Limit Value (TLV) industrial work place standard (Reference: American Conference of Government Industrial Hygienists, 6500 Glenway, Building D-7, and Cincinnati, OH 45211-4438).